

header
SUNFLOWER

INTEGRATIVE TECHNICAL DATA SHEET FOR SUNFLOWER HEADER

MODEL		500 N	600 N	670 N	740 N	940 N	1200 N
dimensions	Height, m	1,1	1,1	1,1	1,1	1,1	1,1
	Max. width, m	5,2	6,2	6,9	7,6	9,4	12,10
	Cutting width, m	5	6	6,7	7,4	9,2	11,90
	Depth, m	2,35	2,35	2,35	2,35	2,35	2,35
	Weight, kg	1.650	1.900	2.000	2.200	2.700	3.200
PTO absorbed power	35/40 Hp	35/40 Hp	35/40 Hp	35/40 Hp	35/40 Hp	35/40 Hp (sx + dx)	
PTO revolutions (approx.)	570	570	570	570	570	570	
Conveyor roller (diameter, mm)	240	240	240	240	300	300	
Spiral Conveyor roller (diameter, mm)	540x500x240	540x500x240	540x500x240	540x500x240	540x500x300	540x500x300	
Conveyor roller drive	mechanical	mechanical	mechanical	mechanical	mechanical	mechanical	
Conveyor roller revolutions (approx.), rpm.	170	170	170	170	170	170	
Oscillating transmission box revolutions, rpm	346	346	346	346	346	346	
Transmission box oil (type)	85W140	85W140	85W140	85W140	85W140	85W140	
Cutting blade strokes (strokes/min)	692	692	692	692	692	692	
Compactor reel	1	1	1	1	1	1	
Compactor reel revolutions (approx.)	45	45	45	45	45	45	
Mounting (type)	central	central	central	central	off-center to the left	central	
Numero di punte	20	24	27	30	38	50	